

# 12.8V24Ah










**LFP Li-ion Battery** 



#### **Dimension:**



#### **SAFETY**

- Cylindrical LiFePO4 cells (32700-6Ah), High consistency, long cycle life and much more safety. UN38.3, CE certification for system.
- The cycle life over 2000 times @80%DOD

#### **DESIGN**

- ABS container, replace VRLA battery perfectly.
- + Fast charge performance.
- -20~+55° C widely temperature range.
- + Maintenance free.

#### **BATTERY MANAGEMENT SYSTEM (BMS)**

- Integrated hardware BMS inside.
- Independent protection for charge and discharge.
- Over voltage, low voltage, over temperature and short circuit protection.

### **Li-ion Battery**



## 12.8V24Ah

#### **Specification**

Model	R-LFP12.8V24Ah
Part Number	8010128002401
Nominal Voltage [V]	12.8
Nominal Capacity [Ah]	24
Total Energy [Wh]	307.2
Max. Charging Current [A]	24
Recommended Charging Current [A]	12
Charging Voltage [V]	14.6
Max. Discharging Current [A]	24
End of Dicharge Voltage [V]	11.2
Pulse Discharge Current	50A @ 10s
Dimension [W*D*H, mm]	181*77*167
Weight [Kg]	3.80
Operation Humidity	0~95% RH (No condensing)
Operating Temperature Range	Charge: $0 \sim +50 ^{\circ}\mathrm{C}$ ; Discharge: $-20 \sim +55 ^{\circ}\mathrm{C}$
BMS Protection	Over charge Over discharge, Over temperature, Short circuit
Parallel Support	Yes, Max 2 Sets
Series Support	Yes, Max 4 Sets
Cycle Life	>2000
Designed Calendar Life	>10 Years
Certification	UN38.3, CE, MSDS

1. 80% DOD and to 80% of initial capacity.

The datasheet is subject to change without prior notification

For more information, contact with: sales@ritarpower.com