


# 8CH PoE NVR

## NVR5-8200P

ossia



5MP



MODEL	NVR5-8200P	
Video	Input	8CH RJ45 Direct Connection / Over Network
	Output	HDMI (4K, 1080P), VGA (1280x1024)
	Decoding	H.265 / H.264
Audio	Input	1CH + Depends on Camera Stream
	Output	1CH + Depends on Camera Stream
	Two Way Audio	Yes
Bandwidth	Incoming	50Mbps
	Outgoing	50Mbps
Recording	Real-Time Recording	8CH 5MP Real-Time
	5MP	240FPS (NTSC)/200FPS (PAL)
	4MP	240FPS (NTSC)/200FPS (PAL)
	3MP	240FPS (NTSC)/200FPS (PAL)
	2MP (1080P)	240FPS (NTSC)/200FPS (PAL)
	1.3MP (960P)	240FPS (NTSC)/200FPS (PAL)
	1MP (720P)	240FPS (NTSC)/200FPS (PAL)
	960H	No
	D1	240FPS (NTSC)/200FPS (PAL)
Playback	Playback Channels	8CH
	Search Mode	Time-Slice, Time, Event, File Management
	USB	1 USB 2.0 Port + 1 USB 3.0 Port
Backup	DVD Burner	No
	Backup Format	AVI/DAT
	Master Stream	Up to 8CH@Recording Resolution
Remote Application	Sub-Stream	Depends on IPC
	Browser	IE, Safari, Firefox (Mac OS, Windows Vista/7/8/10)
	CMS	Yes
	Mobile Application	Provision CAM2 for iPhone/Android Phones/Tablets
Alarm	User Access	10 Users Online with Professional Authority Management
	Input	Depends on Camera
Storage	Output	Depends on Camera
	HDD	1 SATA (6TB)
PTZ	E-SATA	No
	Connection	Via Network
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
Network	RS-485	No
	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P
PoE	ONVIF	Yes
	Ports	Yes (8CH)
	Interface	10/100Mbps
	Standard	IEEE802.3AF
	Total Power	120W (Average 12.5W per Channel)
Others	Max. Power Output (Per Ch.)	~14W
	Power Supply	DC48V/2.5A
	Power Consumption (No HDD)	5W
	Dimension	W300xD250xH45mm
Operation Temperature	0°C ~50°C	