



**2200 R**



**2350 RJ**



[www.ommelift.dk](http://www.ommelift.dk)

## **CRAWLER MOUNTED BOOM PLATFORM**

**OMMELIFT**



Quality since 1906

OMME LIFT A/S – Lægårdsvej 4 – DK 7260 Sdr. Omme  
Phone: + 45 753 413 00 – Fax: + 45 753 415 92  
E-mail: [omme@ommelift.dk](mailto:omme@ommelift.dk) – Web: [www.ommelift.com](http://www.ommelift.com)

Technical Data:	2200 RB	2200 RBD	2350 R(B)(D)J
Max. working height	21.8 m		23.2 m
Max. platform height	19.8 m		21.2 m
Max. outreach	12.2 m		
Up and over clearance	-		
Jib length (jib + basket)	-		2.7 m
Vertical jib rotation	-		90°
Turret rotation	± 355°		
Basket rotation	± 41°		
Max. basket load	200 kg		
Basket size	1.25 x 0.8 x 1.1 m		
Travelling length	5.69 / 6.44 m		5.88 / 6.63 m
Travelling height	1.99 m		
Travelling width	1.10 m		
Operational width	Wide - Wide Min. 4.59 m – max. 5.32 m		
Stabilizer pad	0.28 x 0.44 m		
	<b>HYBRID</b>		
Diesel engine Kubota D722	14kW/18.8hp		
Fuel tank capacity	23 l		
Generator	24 V / 22 A		
Battery pack	24V/400Ah/5h	24V/200Ah/5h	
Transformer (240V only)	Standard	Optional	
Charger	24 V / 30 A		
	Diesel only version available		
See <a href="http://www.ommelift.com">www.ommelift.com</a> for all features and options			
Gradeability, max. across slope	25% (14.0°)		
Gradeability, max. up and down slope	35% (19.3°)		
Set-up ability on uneven ground	40% (21.8°)		
Crawler track length	1.42 m		
Rollers on each side	3		
Total weight	3050 kg		3150 kg
Live load in transit position	379 kg/m <sup>2</sup>		376 kg/m <sup>2</sup>
Live load in working position (including max. basket load)	202 kg/m <sup>2</sup>		208 kg/m <sup>2</sup>
Ground pressure, tracks (Hard surface)	0.62 kg/cm <sup>2</sup> (2.50 kg/cm <sup>2</sup> )		0.64 kg/cm <sup>2</sup> (2.50 kg/cm <sup>2</sup> )
Ground pressure, outrigger	1.46 kg/cm <sup>2</sup>		1.48 kg/cm <sup>2</sup>
Max. force, outrigger	18.0 kN		18.3 kN

