



אל פסק PARTNER VISION

תכונות

- מטען חכם להארכת חיי המצבר והפחתת זמן הטעינה ב- 50%
- מעבד איכותי להבטחת אמינות גבוהה
- מייצב מתח רב דרגתי המתאים לרשת החשמל בישראל
- הפעלה אוטומטית בעת חזרת החשמל
- גל מוצא- דמוי גל סינוס
- טעינת מצברים גם כאשר המכשיר כבוי
- התנעה קרה
- ממשק תקשורת USB לכיבוי מסודר של המחשב
- 5 שנות אחריות לאלקטרוניקה, שנתיים למצברים

Specifications

Model	PRV650	PRV850	PRV1000
Capacity	650VA/360W	850VA/480W	1000VA/600W
Input			
Voltage	110/120 VAC or 220/230/240 VAC		
VoltageRange	81-145 VAC / 162-290 VAC		
FrequencyRange	60/50 Hz (auto sensing)		
Output			
AC Voltage Regulation (Line.mode)	±15%		
AC Voltage Regulation (Batt.mode)	±10%		
FrequencyRange (Batt.mode)	60 Hz or 50 Hz ±1 Hz		
Transfer Time	Typical 2-6 ms		
Wavwform (Batt.mode)	Simulated Sine Wave		
Battery			
Typical Recharge Time	4-6 hours recover 90% capacity		
Indicators			
Led Disply	AC Mode	Green lighting	
	Battery Mode	Yellow flashing	
	Fault	Red lighting	
Protection			
Spike Protection	300 Jouls		
Full Protection	Overload, discharge, and overcharge protection		
Alarm			
Battery Mode	Sounding every 10 secondes		
Low Battery	Sounding every second		
Overload	Sounding every 0.5 second		
Battery Replacement Alarm	Sounding every 2 second		
Fault	Continuously sounding		
Physical			
Dimension DxWxH (mm)	287 x 100 x 142		350 x 146 x 160
Net Weight (kgs)	4.25	4.5	8.0
Operating Environment			
Humidity	0-90 % RH @ 0-40°C (non- condensing)		
Noise Level	Less than 40dB		
Management			
USB	Support Windows 98 SE / ME / NT 4.x / 2000 / 2003 / XP / Vista / 2008/7/8/10 Linux according software list		

* Product specifications are subject to change without further notice